



RealCurrent

The Power Company

Model	SE 17KTL-D3	SE 20KTL-D3	SE 22KTL-D3
Efficiency			
Max. Efficiency	98.6%	98.6%	98.6%
European Efficiency	98.2%	97.7%	98.2%
Input(PV)			
Max. Input Voltage		1000V	
Max. PV configuration (STC)		150%	
Rated Input Voltage		620V	
Max. Input Current		54A(2*27A)	
Max. Short Circuit Current		60A(2*30A)	
Start Input Voltage		250V	
MPPT Operating Voltage Range		180V-960V	
Max. Number of PV Strings		4(2/2)	
No. of MPPTs		2	
Output(Grid)			
Rated AC Active Power	17,000W	20,000W	22,000W
Max. AC Apparent Power	18,700VA	22,000VA	24,200VA
Max. AC Active Power (PF=1)	18,700VA	22,000W	24,200W
Max. AC Output Current	3*28.3A	3*33.5A	3*35A
Rated AC Voltage		380V/400V, 3W+N+PE	
AC Voltage Range ①		277V-520V (Adjustable)	
Rated Grid Frequency		50Hz / 60Hz	
Grid Frequency Range ②		45Hz-55Hz / 55Hz-65Hz (Adjustable)	
THDI		<3% (Rated Power)	
DC Current Injection		<0.5%In	
Power Factor		>0.99 Rated power (Adjustable 0.8 LG - 0.8 LD)	
Protection			
DC switch		Support	
Anti-islanding protection		Support	
AC overcurrent protection		Support	
AC short circuit protection		Support	
DC reverse connection		Support	
Surge Arrester		DC Type II / AC Type II	
Insulation detection		Support	
Leakage current protection		Support	
General			
Topology		Transformerless	
IP Rating		IP65	
Night Self Consumption		<1W	
Cooling		Natural cooling	
Operating Temperature Range		-25°C-60°C	
Relative Humidity Range		0-100%	
Max. Operating Altitude		4000m	
Noise		<30dB	
Dimensions (W*H*D)		555mm*446mm*270mm	
Weight		35kg	
HMI & COM			
Display		Wireless & APP+LED, LCD (Optional)	
Communication		RS485, WiFi / GPRS / 4G / LAN (Optional)	
Certification			
Safety		IEC62109-1, IEC62109-2	
Grid Code		IEC61727/62116	
Warranty		5 Years	

Remarks: • ①② The range of output voltage and frequency may vary depending upon different grid codes
• Specifications are subject to change without advance notice



RealCurrent

The Power Company

THREE PHASE & DUAL MPPT SE 17/20/22KTL-D3

Application: Small-sized Industrial and Residential Use

